

OpcClassicApplicationDescription Members

Namespace: Opc.UaFx.Classic

Assemblies: Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll

The [OpcClassicApplicationDescription](#) type exposes the following members.

Constructors

OpcClassicApplicationDescription(Guid)

C#

```
public OpcClassicApplicationDescription(Guid classId)
```

Parameters

classId Guid

OpcClassicApplicationDescription(Guid, String)

C#

```
public OpcClassicApplicationDescription(Guid classId, string progId)
```

Parameters

classId Guid

progId String

OpcClassicApplicationDescription(Guid, String, String)

C#

```
public OpcClassicApplicationDescription(Guid classId, string progId, string host)
```

Parameters

classId Guid

progId String

host String

Properties

ClassId

C#

```
public Guid ClassId { get; }
```

Property Value

Guid

Host

C#

```
public string Host { get; }
```

Property Value

String

HostIdentity

C#

```
public OpcClassicIdentity HostIdentity { get; set; }
```

Property Value

OpcClassicIdentity

Name

C#

```
public string Name { get; set; }
```

Property Value

[String](#)

ProgId

C#

```
public string ProgId { get; }
```

Property Value

[String](#)

Uri

C#

```
public Uri Uri { get; }
```

Property Value

[Uri](#)

Methods

Create(Uri)

C#

```
public static OpcClassicApplicationDescription Create(Uri uri)
```

Parameters

uri [Uri](#)

Returns

[OpcClassicApplicationDescription](#)

Exceptions

[ArgumentException](#)

[ArgumentNullException](#)

TryCreate(Uri, out OpcClassicApplicationDescription)

C#

```
public static bool TryCreate(Uri uri, out OpcClassicApplicationDescription result)
```

Parameters

uri Uri

result OpcClassicApplicationDescription

Returns

Boolean

Table of Contents

Constructors	1
OpcClassicApplicationDescription(Guid)	1
OpcClassicApplicationDescription(Guid, String)	1
OpcClassicApplicationDescription(Guid, String, String)	1
Properties	2
ClassId	2
Host	2
HostIdentity	2
Name	2
ProgId	3
Uri	3
Methods	3
Create(Uri)	3
TryCreate(Uri, out OpcClassicApplicationDescription)	4

