

# OpcAddObjectNode Class

**Namespace:** Opc.UaFx

**Assemblies:** Opc.UaFx.Advanced.dll

Defines a single command of the [IOpcAddNodesService](#) used to add one object node (nodes of the category [Object](#)).

**C#**

```
public class OpcAddObjectNode : OpcAddInstanceNode
```

**Inheritance** [Object](#) > [OpcServiceCommand](#) > [OpcNodeServiceCommand](#) > [OpcAddNode](#) > [OpcAddInstanceNode](#) > [OpcAddObjectNode](#)

**Derived**

- [OpcAddFolderNode](#)

## Constructors

Name	Description
<a href="#">OpcAddObjectNode(OpcName)</a>	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add. The according <a href="#">OpcNodeId</a> to identify and access the new node is determined by the service. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.
<a href="#">OpcAddObjectNode(OpcName, OpcAddInstanceNode)</a>	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add. The according <a href="#">OpcNodeId</a> to identify and access the new node is determined by the service. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.
<a href="#">OpcAddObjectNode(OpcName, OpcNodeId)</a>	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.
<a href="#">OpcAddObjectNode(OpcName, OpcNodeId, OpcAddInstanceNode)</a>	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.
<a href="#">OpcAddObjectNode(OpcName, OpcNodeId, OpcNodeId)</a>	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the node identified by <b>parentNodeId</b> using <a href="#">HasComponent</a> as the type of reference.

Name	Description
OpcAddObjectNode(OpcName, OpcNodeId, OpcNodeId, OpcAddInstanceNode)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the node identified by <b>parentNodeId</b> using <a href="#">HasComponent</a> as the type of reference.
OpcAddObjectNode(OpcName, OpcNodeId, OpcNodeId, OpcNodeId)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the node identified by <b>parentNodeId</b> using the type of reference identified by the <b>referenceTypeId</b> specified.
OpcAddObjectNode(OpcName, OpcNodeId, OpcNodeId, OpcNodeId, OpcAddInstanceNode)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the node identified by <b>parentNodeId</b> using the type of reference identified by the <b>referenceTypeId</b> specified.
OpcAddObjectNode(OpcName, OpcNodeId, OpcNodeId, OpcReferenceType)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the node identified by <b>parentNodeId</b> using the <b>referenceType</b> specified as the type of reference.
OpcAddObjectNode(OpcName, OpcNodeId, OpcNodeId, OpcReferenceType, OpcAddInstanceNode)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the <b>name</b> of the object node to add, which shall be additionally accessible by the <b>nodeId</b> defined. The new node will be a child of the node identified by <b>parentNodeId</b> using the <b>referenceType</b> specified as the type of reference.
OpcAddObjectNode(OpcNodeId, OpcName)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the specified <b>typeDefinitionId</b> of object node to add, which shall be accessible by the <b>name</b> defined. The according <b>OpcNodeId</b> to identify and access the new node is determined by the service. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.
OpcAddObjectNode(OpcNodeId, OpcName, OpcAddInstanceNode)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the specified <b>typeDefinitionId</b> of object node to add, which shall be accessible by the <b>name</b> defined. The according <b>OpcNodeId</b> to identify and access the new node is determined by the service. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.
OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the specified <b>typeDefinitionId</b> of object node to add, which shall be accessible by the <b>name</b> and <b>nodeId</b> defined. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.
OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId, OpcAddInstanceNode)	Initializes a new instance of the <a href="#">OpcAddObjectNode</a> class using the specified <b>typeDefinitionId</b> of object node to add, which shall be accessible by the <b>name</b> and <b>nodeId</b> defined. The new node will be a child of the <a href="#">ObjectsFolder</a> node using <a href="#">HasComponent</a> as the type of reference.

Name	Description
<p><code>OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId, OpcNodeId)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>typeDefinitionId</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using <code>HasComponent</code> as the type of reference.</p>
<p><code>OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId, OpcNodeId, OpcAddInstanceNode)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>typeDefinitionId</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using <code>HasComponent</code> as the type of reference.</p>
<p><code>OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId, OpcNodeId, OpcNodeId)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>typeDefinitionId</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the type of reference identified by the <code>referenceTypeId</code> specified.</p>
<p><code>OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId, OpcNodeId, OpcNodeId, OpcAddInstanceNode)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>typeDefinitionId</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the type of reference identified by the <code>referenceTypeId</code> specified.</p>
<p><code>OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId, OpcNodeId, OpcReferenceType)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>typeDefinitionId</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the <code>referenceType</code> specified as the type of reference.</p>
<p><code>OpcAddObjectNode(OpcNodeId, OpcName, OpcNodeId, OpcNodeId, OpcReferenceType, OpcAddInstanceNode)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>typeDefinitionId</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the <code>referenceType</code> specified as the type of reference.</p>
<p><code>OpcAddObjectNode(OpcObjectType, OpcName)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> defined. The according <code>OpcNodeId</code> to identify and access the new node is determined by the service. The new node will be a child of the <code>ObjectsFolder</code> node using <code>HasComponent</code> as the type of reference.</p>
<p><code>OpcAddObjectNode(OpcObjectType, OpcName, OpcAddInstanceNode)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> defined. The according <code>OpcNodeId</code> to identify and access the new node is determined by the service. The new node will be a child of the <code>ObjectsFolder</code> node using <code>HasComponent</code> as the type of reference.</p>
<p><code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId)</code></p>	<p>Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the <code>ObjectsFolder</code> node using <code>HasComponent</code> as the type of reference.</p>

Name	Description
<code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId, OpcAddInstanceNode)</code>	Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the <code>ObjectsFolder</code> node using <code>HasComponent</code> as the type of reference.
<code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId, OpcNodeId)</code>	Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using <code>HasComponent</code> as the type of reference.
<code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId, OpcNodeId, OpcAddInstanceNode)</code>	Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using <code>HasComponent</code> as the type of reference.
<code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId, OpcNodeId, OpcNodeId)</code>	Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the type of reference identified by the <code>referenceTypeId</code> specified.
<code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId, OpcNodeId, OpcNodeId, OpcAddInstanceNode)</code>	Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the type of reference identified by the <code>referenceTypeId</code> specified.
<code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId, OpcNodeId, OpcReferenceType)</code>	Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the <code>referenceType</code> specified as the type of reference.
<code>OpcAddObjectNode(OpcObjectType, OpcName, OpcNodeId, OpcNodeId, OpcReferenceType, OpcAddInstanceNode)</code>	Initializes a new instance of the <code>OpcAddObjectNode</code> class using the specified <code>type</code> of object node to add, which shall be accessible by the <code>name</code> and <code>nodeId</code> defined. The new node will be a child of the node identified by <code>parentNodeId</code> using the <code>referenceType</code> specified as the type of reference.

## Properties

Name	Description
<code>Category</code>	Gets a value indicating the classification of the node in the address space. (Inherited from <code>OpcAddNode</code> )
<code>Children</code>	Gets a collection of <code>OpcAddNode</code> instances which define the sub-ordinated nodes to add as children to the node to add. (Inherited from <code>OpcAddInstanceNode</code> )
<code>Description</code>	Gets or sets the localized description of the meaning of the node. (Inherited from <code>OpcAddNode</code> )
<code>DisplayName</code>	Gets or sets the localized name of the node. (Inherited from <code>OpcAddNode</code> )
<code>Name</code>	Gets the non-localised human-readable name of the node in the address space. (Inherited from <code>OpcAddNode</code> )

Name	Description
Nodeld	Gets the node identifier of the node on which a node orientated service have to operate on. (Inherited from <a href="#">OpcNodeServiceCommand</a> )
ParentNodeld	Gets the identifier of the existing parent node of the new node. (Inherited from <a href="#">OpcAddNode</a> )
ReferenceType	Gets a value which defines a pre-defined used <a href="#">ReferenceTypeld</a> as one of the members defined by the <a href="#">OpcReferenceType</a> enumeration to simplify querying standard reference types. (Inherited from <a href="#">OpcAddInstanceNode</a> )
ReferenceTypeld	Gets the identifier which identifies the node that defines the semantic of the reference between a source and a target node and generally reflects an operation between the two, such as "A contains B". (Inherited from <a href="#">OpcAddInstanceNode</a> )
SupportsNullNodeld	Gets a value indicating whether the <a href="#">OpcNodeServiceCommand</a> supports instances of the <a href="#">OpcNodeld</a> class its <a href="#">IsNull</a> provides a value equals to the value true. (Inherited from <a href="#">OpcNodeServiceCommand</a> )
SupportsNullNodeld	Gets a value indicating whether the <a href="#">OpcAddNode</a> supports instances of the <a href="#">OpcNodeld</a> class its <a href="#">IsNull</a> provides a value equals to the value true. (Inherited from <a href="#">OpcAddNode</a> )
Type	Gets value indicating the predefined underlying type definition the new node will represent an instance of.
TypeDefinitionId	Gets the identifier which identifies the node that defines the underlying node type from that the instance node is to be created. (Inherited from <a href="#">OpcAddInstanceNode</a> )
UserWriteAccess	Gets or sets a value which exposes the possibilities of a client to write the attributes of the node taking user access rights into account. (Inherited from <a href="#">OpcAddNode</a> )
WriteAccess	Gets or sets a value which exposes the possibilities of a client to write the attributes of the node without taking user access rights into account. (Inherited from <a href="#">OpcAddNode</a> )

## Methods

Name	Description
<a href="#">DenyNullIdentifier(OpcNodeld, String)</a>	Verifies whether the <b>value</b> is a null identifier by checking the <a href="#">IsNull</a> property. (Inherited from <a href="#">OpcNodeServiceCommand</a> )
<a href="#">OfType(OpcNodeld)</a>	Retrieves an instance which represents the definition of an object type that can be used to define <a href="#">OpcAddObjectNode</a> command instances using the type of object node represented by the <a href="#">TypeDefinition</a> instance provided.



# Table of Contents

<b>Constructors</b> .....	1
<b>Properties</b> .....	4
<b>Methods</b> .....	5