

OpcDataVariableNode Members

Namespace: Opc.UaFx

Assemblies: Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll

The [OpcDataVariableNode](#) type exposes the following members.

Constructors

OpcDataVariableNode(IOpcNode, OpcName)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the **name** specified as a child node of the **parent** node given.

C#

```
public OpcDataVariableNode(IOpcNode parent, OpcName name)
```

Parameters

parent [IOpcNode](#)

The [IOpcNode](#) used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

name [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

OpcDataVariableNode(IOpcNode, OpcName, Object)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the **name** specified with the initial value defined by **value** as a child node of the **parent** node given.

C#

```
public OpcDataVariableNode(IOpcNode parent, OpcName name, object value)
```

Parameters

parent [IOpcNode](#)

The [IOpcNode](#) used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

name [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

value [Object](#)

The initial value of the new data variable node.

OpcDataVariableNode(IOpcNode, OpcName, OpcNodeId)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the [name](#) and [id](#) specified as a child node of the [parent](#) node given.

C#

```
public OpcDataVariableNode(IOpcNode parent, OpcName name, OpcNodeId id)
```

Parameters

[parent](#) [IOpcNode](#)

The [IOpcNode](#) used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

[name](#) [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

[id](#) [OpcNodeId](#)

The [OpcNodeId](#) through that the new data variable node can be identified and accessed.

OpcDataVariableNode(IOpcNode, OpcName, OpcNodeId, Object)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the [name](#) and [id](#) specified with the initial value defined by [value](#) as a child node of the [parent](#) node given.

C#

```
public OpcDataVariableNode(IOpcNode parent, OpcName name, OpcNodeId id, object value)
```

Parameters

[parent](#) [IOpcNode](#)

The [IOpcNode](#) used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

[name](#) [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

[id](#) [OpcNodeId](#)

The [OpcNodeId](#) through that the new data variable node can be identified and accessed.

[value](#) [Object](#)

The initial value of the new data variable node.

OpcDataVariableNode(OpcName)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the **name** specified.

C#

```
public OpcDataVariableNode(OpcName name)
```

Parameters

name [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

OpcDataVariableNode(OpcName, Object)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the **name** specified with the initial value given by **value**.

C#

```
public OpcDataVariableNode(OpcName name, object value)
```

Parameters

name [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

value [Object](#)

The initial value of the new data variable node.

OpcDataVariableNode(OpcName, OpcNodeId)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the **name** and **id** specified.

C#

```
public OpcDataVariableNode(OpcName name, OpcNodeId id)
```

Parameters

name [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

id [OpcNodeId](#)

The [OpcNodeId](#) through that the new data variable node can be identified and accessed.

OpcDataVariableNode(OpcName, OpcNodeId, Object)

Initializes a new instance of the [OpcDataVariableNode](#) class accessible by the [name](#) and [id](#) specified with the initial value given by [value](#).

C#

```
public OpcDataVariableNode(OpcName name, OpcNodeId id, object value)
```

Parameters

[name](#) [OpcName](#)

The [OpcName](#) through that the new data variable node can be accessed.

[id](#) [OpcNodeId](#)

The [OpcNodeId](#) through that the new data variable node can be identified and accessed.

[value](#) [Object](#)

The initial value of the new data variable node.

Properties

DefaultTypeDefinitionId

Gets the default identifier which identifies the node that defines the underlying node type from that this [OpcInstanceNode](#) has been created.

C#

```
protected override OpcNodeId DefaultTypeDefinitionId { get; }
```

Property Value

[OpcNodeId](#)

The [OpcNodeId](#) of the type node from that this [OpcInstanceNode](#) has been created from. These type node defines the typical structure of an instance node of its type definition. If there exists no specific type definition node a null reference (Nothing in Visual Basic).

Table of Contents

Constructors	1
OpcDataVariableNode(IOpcNode, OpcName)	1
OpcDataVariableNode(IOpcNode, OpcName, Object)	1
OpcDataVariableNode(IOpcNode, OpcName, OpcNodeId)	2
OpcDataVariableNode(IOpcNode, OpcName, OpcNodeId, Object)	2
OpcDataVariableNode(OpcName)	3
OpcDataVariableNode(OpcName, Object)	3
OpcDataVariableNode(OpcName, OpcNodeId)	3
OpcDataVariableNode(OpcName, OpcNodeId, Object)	4
Properties	4
DefaultTypeDefinitionId	4

