

OpcDialogResponseMethodNode

Members

Namespace: Opc.UaFx

Assemblies: Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll

The [OpcDialogResponseMethodNode](#) type exposes the following members.

Constructors

OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcDialogResponseMethodNode.DialogResponseCallback)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class accessible by the **name** specified with the [DialogResponseCallback](#) call given by **callback** as a child node of the **parent** node given.

C#

```
public OpcDialogResponseMethodNode(IOpcNode parent, OpcName name,
OpcDialogResponseMethodNode.DialogResponseCallback callback)
```

Parameters

parent [IOpcNode](#)

The [IOpcNode](#) used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

name [OpcName](#)

The [OpcName](#) through that the new dialog response method node can be accessed.

callback [DialogResponseCallback](#)

The [DialogResponseCallback](#) to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcDialogResponseMethodNode.DialogResponseExCallback)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class accessible by the **name** specified with the [DialogResponseExCallback](#) call given by **callback** as a child node of the **parent** node given.

C#

```
public OpcDialogResponseMethodNode(IOpcNode parent, OpcName name,
OpcDialogResponseMethodNode.DialogResponseExCallback callback)
```

Parameters

parent IOpcNode

The IOpcNode used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

name OpcName

The OpcName through that the new dialog response method node can be accessed.

callback DialogResponseExCallback

The DialogResponseExCallback to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseCallback)

Initializes a new instance of the OpcDialogResponseMethodNode class accessible by the name and id specified with the delegate to call defined by callback as a child node of the parent node given.

C#

```
public OpcDialogResponseMethodNode(IOpcNode parent, OpcName name, OpcNodeId id, OpcDialogResponseMethodNode.DialogResponseCallback callback)
```

Parameters

parent IOpcNode

The IOpcNode used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

name OpcName

The OpcName through that the new dialog response method node can be accessed.

id OpcNodeId

The OpcNodeId through that the new dialog response method node can be identified and accessed.

callback DialogResponseCallback

The DialogResponseCallback to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseExCallba

ck)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class accessible by the [name](#) and [id](#) specified with the delegate to call defined by [callback](#) as a child node of the [parent](#) node given.

C#

```
public OpcDialogResponseMethodNode(IOpcNode parent, OpcName name, OpcNodeId id,
OpcDialogResponseMethodNode.DialogResponseExCallback callback)
```

Parameters

[parent](#) [IOpcNode](#)

The [IOpcNode](#) used as the parent node or a null reference (Nothing in Visual Basic) in the case there is no parent node available.

[name](#) [OpcName](#)

The [OpcName](#) through that the new dialog response method node can be accessed.

[id](#) [OpcNodeId](#)

The [OpcNodeId](#) through that the new dialog response method node can be identified and accessed.

[callback](#) [DialogResponseExCallback](#)

The [DialogResponseExCallback](#) to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(OpcDialogResponseMethodNode.DialogResponseCallback)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class with the [DialogResponseCallback](#) call given by [callback](#).

C#

```
public OpcDialogResponseMethodNode(OpcDialogResponseMethodNode.DialogResponseCallback
callback)
```

Parameters

[callback](#) [DialogResponseCallback](#)

The [DialogResponseCallback](#) to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(OpcDialogResponseMethodNode.DialogResponseExCallback)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class with the [DialogResponseExCallback](#) call given by [callback](#).

C#

```
public OpcDialogResponseMethodNode(OpcDialogResponseMethodNode.DialogResponseExCallback
callback)
```

Parameters

callback [DialogResponseExCallback](#)

The [DialogResponseExCallback](#) to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(OpcName, OpcDialogResponseMethodNode.DialogResponseCallback)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class accessible by the **name** specified with the [DialogResponseCallback](#) call given by **callback**.

C#

```
public OpcDialogResponseMethodNode(OpcName name,
OpcDialogResponseMethodNode.DialogResponseCallback callback)
```

Parameters

name [OpcName](#)

The [OpcName](#) through that the new dialog response method node can be accessed.

callback [DialogResponseCallback](#)

The [DialogResponseCallback](#) to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(OpcName, OpcDialogResponseMethodNode.DialogResponseExCallba ck)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class accessible by the **name** specified with the [DialogResponseExCallback](#) call given by **callback**.

C#

```
public OpcDialogResponseMethodNode(OpcName name,
OpcDialogResponseMethodNode.DialogResponseExCallback callback)
```

Parameters

name [OpcName](#)

The [OpcName](#) through that the new dialog response method node can be accessed.

callback [DialogResponseExCallback](#)

The [DialogResponseExCallback](#) to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseCallback)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class accessible by the [name](#) and [id](#) specified with the delegate to call given by [callback](#).

C#

```
public OpcDialogResponseMethodNode(OpcName name, OpcNodeId id,
OpcDialogResponseMethodNode.DialogResponseCallback callback)
```

Parameters

[name](#) [OpcName](#)

The [OpcName](#) through that the new dialog response method node can be accessed.

[id](#) [OpcNodeId](#)

The [OpcNodeId](#) through that the new dialog response method node can be identified and accessed.

[callback](#) [DialogResponseCallback](#)

The [DialogResponseCallback](#) to call on method invocation of the new dialog response method node.

OpcDialogResponseMethodNode(OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseExCallback)

Initializes a new instance of the [OpcDialogResponseMethodNode](#) class accessible by the [name](#) and [id](#) specified with the delegate to call given by [callback](#).

C#

```
public OpcDialogResponseMethodNode(OpcName name, OpcNodeId id,
OpcDialogResponseMethodNode.DialogResponseExCallback callback)
```

Parameters

[name](#) [OpcName](#)

The [OpcName](#) through that the new dialog response method node can be accessed.

[id](#) [OpcNodeId](#)

The [OpcNodeId](#) through that the new dialog response method node can be identified and accessed.

[callback](#) [DialogResponseExCallback](#)

The [DialogResponseExCallback](#) to call on method invocation of the new dialog response method node.

Properties

DefaultTypeDefinitionId

Gets the default identifier which identifies the node that defines the underlying node type from that this [OpcInstanceNode](#) has been created.

C#

```
protected override OpcNodeId DefaultTypeDefinitionId { get; }
```

Property Value

[OpcNodeId](#)

The [OpcNodeId](#) of the type node from that this [OpcInstanceNode](#) has been created from. These type node defines the typical structure of an instance node of its type definition. If there exists no specific type definition node a null reference (Nothing in Visual Basic).

Table of Contents

Constructors	1
OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcDialogResponseMethodNode.DialogResponseCallback)	1
OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcDialogResponseMethodNode.DialogResponseExCallback)	1
OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseCallback)	2
OpcDialogResponseMethodNode(IOpcNode, OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseExCallback)	2
OpcDialogResponseMethodNode(OpcDialogResponseMethodNode.DialogResponseCallback)	3
OpcDialogResponseMethodNode(OpcDialogResponseMethodNode.DialogResponseExCallback)	3
OpcDialogResponseMethodNode(OpcName, OpcDialogResponseMethodNode.DialogResponseCallback)	4
OpcDialogResponseMethodNode(OpcName, OpcDialogResponseMethodNode.DialogResponseExCallback)	4
OpcDialogResponseMethodNode(OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseCallback)	5
OpcDialogResponseMethodNode(OpcName, OpcNodeId, OpcDialogResponseMethodNode.DialogResponseExCallback)	5
Properties	6
DefaultTypeDefinitionId	6

