OpcEventNodeSnapshot Class

Namespace: Opc.UaFx
Assemblies: Opc.UaFx.Advanced.dll

Defines a lightweight immutable deep snapshot of a whole 'Opc.UaFx.OpcEventNode'.

C#

```
public class OpcEventNodeSnapshot : OpcInstanceNodeSnapshot, IOpcReadOnlyNodeDataStore
```

Inheritance Object › OpcInstanceNodeSnapshot › OpcEventNodeSnapshot

Implements IOpcReadOnlyNodeDataStore

Properties

Name	Description
EventTypeId	Gets the node identifier identifying the type of 'Opc.UaFx.OpcEventNode' the OpcEventNodeSnapshot belong to.
Tag	Gets or sets the object that contains additional user data about the snapshot. (Inherited from OpcInstanceNodeSnapshot)

Methods

Name	Description
Create(OpcContext, OpcEventNode)	Creates a new OpcEventNodeSnapshot from the `node` specified.
Create(OpcContext, OpcInstanceNode)	Creates a new OpcInstanceNodeSnapshot from the `node` specified. (Inherited from OpcInstanceNodeSnapshot)
Get``1(OpcAttribute, OpcName)	Retrieves the value of the `attribute` of the element browsable through the `name` specified. (Inherited from OpcInstanceNodeSnapshot)
Get``1(OpcAttribute, OpcName)	Retrieves the value of the `attribute` of the element browsable through the `pathElements` specified. (Inherited from OpcInstanceNodeSnapshot)
Get``1(OpcAttribute, OpcNamePath)	Retrieves the value of the `attribute` of the element browsable through the `path` specified. (Inherited from OpcInstanceNodeSnapshot)
Get``1(OpcAttribute, String)	Retrieves the value of the `attribute` of the element browsable through the `name` specified. (Inherited from OpcInstanceNodeSnapshot)
Get``1(OpcName)	Retrieves the Value attribute of the element browsable through the `name` specified. (Inherited from OpcInstanceNodeSnapshot)
Get``1(String)	Retrieves the Value attribute of the element browsable through the `name` specified. (Inherited from OpcInstanceNodeSnapshot)

Table of Contents

Properties 1
Methods 1