OpcFolderNode Class

Namespace: Opc.UaFx
Assemblies: Opc.UaFx.Advanced.dll

Defines a node to organise the address space into a hierarchy of nodes. They represent the root node of a subtree, and have no other semantics associated with them.

C#

```
public class OpcFolderNode : OpcObjectNode, IOpcNode, IOpcNodeInfo
```

Inheritance Object › OpcNode › OpcInstanceNode › OpcObjectNode › OpcFolderNode

Implements IOpcNode, IOpcNodeInfo

Constructors

Name	Description
OpcFolderNode(IOpcNode, OpcName)	Initializes a new instance of the OpcFolderNode class accessible by the `name` specified as a child node of the `parent` node given.
OpcFolderNode(IOpcNode, OpcName, OpcInstanceNode)	Initializes a new instance of the OpcFolderNode class accessible by the `name` specified as a child node of the `parent` node given and with the initial child nodes specified by `children`.
OpcFolderNode(IOpcNode, OpcName, OpcNodeId)	Initializes a new instance of the OpcFolderNode class accessible by the `name` and `id` specified as a child node of the `parent` node given.
OpcFolderNode(IOpcNode, OpcName, OpcNodeId, OpcInstanceNode)	Initializes a new instance of the OpcFolderNode class accessible by the `name`, `id` specified as a child node of the `parent` node given and with the initial child nodes specified by `children`.
OpcFolderNode(OpcName)	Initializes a new instance of the OpcFolderNode class accessible by the `name` specified.
OpcFolderNode(OpcName, OpcInstanceNode)	Initializes a new instance of the OpcFolderNode class accessible by the `name` and with the initial child nodes specified by `children`.
OpcFolderNode(OpcName, OpcNodeId)	Initializes a new instance of the OpcFolderNode class accessible by the `name` and `id` specified.
OpcFolderNode(OpcName, OpcNodeId, OpcInstanceNode)	Initializes a new instance of the OpcFolderNode class accessible by the `name`, `id` and with the initial child nodes specified by `children`.

Events

Name	Description
AfterApplyChanges	Occurs after one or more changes on the node has been notified. (Inherited from OpcNode)

Name	Description
BeforeApplyChanges	Occurs before one or more changes on the node are notified. (Inherited from OpcNode)

Properties

Name	Description
Category	Gets the NodeCategoryOpcAttribute which identifies the kind of node and is therefore used to classify the node regarding its use and purpose. (Inherited from OpcNode)
DefaultReferenceTypeId	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node.
DefaultReferenceTypeId	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node. (Inherited from OpcInstanceNode)
DefaultReferenceTypeId	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node. (Inherited from OpcObjectNode)
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created.
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcInstanceNode)
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcObjectNode)
Description	Gets or sets the value of the optional DescriptionOpcAttribute which shall explain the meaning of the node. (Inherited from OpcNode)
Descriptions	Gets the OpcNodeGlobalization instance used to control the localization and other globalization related tasks for the Description attribute of the current node. (Inherited from OpcNode)
DisplayName	Gets or sets the value of the DisplayNameOpcAttribute which defines the localizable name of the node. (Inherited from OpcNode)
DisplayNames	Gets the OpcNodeGlobalization instance used to control the localization and other globalization related tasks for the DisplayName attribute of the current node. (Inherited from OpcNode)
HasPendingChanges	Gets a value indiciating whether there exists any pending change on the node. (Inherited from OpcNode)
Id	Gets the value of the NodeIdOpcAttribute which unambiguously identifies the node. (Inherited from OpcNode)
ModellingRuleId	Gets or sets the identifier which defines how the OpcInstanceNode is used for instantiation. (Inherited from OpcInstanceNode)

Name	Description
Name	Gets or sets the value of the BrowseNameOpcAttribute which defines the non-localizable human-readable name used when browsing the address space. (Inherited from OpcNode)
Namespace	(Inherited from OpcNode)
Parent	Gets the parent node of the node. (Inherited from OpcNode)
Parent	Gets the parent node of the node. (Inherited from OpcInstanceNode)
PendingChanges	Gets a value indicating the most recent changes performed on the node since their last notification. (Inherited from OpcNode)
QueryEventsCallback	Gets or sets a callback used to query any event information which belongs to the node. (Inherited from OpcNode)
ReadDescriptionCallback	(Inherited from OpcNode)
ReadDisplayNameCallback	(Inherited from OpcNode)
ReadUserWriteAccessCallback	(Inherited from OpcNode)
ReadWriteAccessCallback	(Inherited from OpcNode)
ReferenceType	Gets a value which defines a pre-defined used ReferenceTypeId as one of the members defined by the OpcReferenceType enumeration to simplify querying standard reference types. (Inherited from OpcInstanceNode)
ReferenceTypeId	Gets or sets the identifier which identifies the node that defines the semantic of the reference between a source and a target node and generally reflects an operation between the two, such as “A contains B”. (Inherited from OpcInstanceNode)
SymbolicName	(Inherited from OpcNode)
Tag	Gets or sets the object that contains additional user data about the node. (Inherited from OpcNode)
TypeDefinitionId	Gets or sets the identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcInstanceNode)
UserWriteAccess	Gets or sets the value of the optional UserWriteAccessOpcAttribute which exposes the possibilities of a client to write the attributes of the node taking user access rights into account. (Inherited from OpcNode)
WriteAccess	Gets or sets the value of the optional WriteAccessOpcAttribute which exposes the posibilities of a client to write the attributes of the node. (Inherited from OpcNode)
WriteDescriptionCallback	(Inherited from OpcNode)
WriteDisplayNameCallback	(Inherited from OpcNode)
WriteUserWriteAccessCallback	(Inherited from OpcNode)
WriteWriteAccessCallback	(Inherited from OpcNode)

Methods

Name	Description
AddChild(OpcContext, OpcInstanceNode)	(Inherited from OpcInstanceNode)
AddNotifier(OpcContext, IOpcNode)	(Inherited from OpcNode)
AddNotifier(OpcContext, IOpcNode)	(Inherited from OpcObjectNode)

Name	Description
ApplyChanges(OpcContext)	Notifies about changes performed on the node since the last notification and resets the pending changes to None. (Inherited from OpcNode)
ApplyChanges(OpcContext, Boolean)	Notifies about changes performed on the node (and optionally on its children) since the last notification and resets the pending changes to None. (Inherited from OpcNode)
AttributeValue(OpcAttribute)	Retrieves the value of the `attribute` specified. (Inherited from OpcNode)
AttributeValue``1(OpcAttribute)	Retrieves the value of the `attribute` specified. (Inherited from OpcNode)
Child(OpcContext, OpcName)	Retrieves the child node its Name property matches exactly the `name` specified. (Inherited from OpcNode)
Children(OpcContext)	Retrieves a sequence of all nodes organized as children of this node. (Inherited from OpcNode)
InitializeDefaults	Initializes the default values used by the node implementation represented / required. (Inherited from OpcNode)
InitializeDefaults	Initializes the default values used by the OpcInstanceNode. (Inherited from OpcInstanceNode)
IsChangePending(OpcNodeChanges)	(Inherited from OpcNode)
OnAfterApplyChanges(OpcNodeChangesEventArgs)	Raises the AfterApplyChanges event using the event data specified. (Inherited from OpcNode)
OnBeforeApplyChanges(OpcNodeChangesEventArgs)	Raises the BeforeApplyChanges event using the event data specified. (Inherited from OpcNode)
QueryEventsCore(OpcNodeContext, OpcEventCollection)	(Inherited from OpcNode)
ReadAttributeValueCore``1(OpcReadAttributeValueContext, OpcAttributeValue)	(Inherited from OpcNode)
RemoveChild(OpcContext, OpcInstanceNode)	(Inherited from OpcInstanceNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcInstanceNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcObjectNode)
ReportEvent(OpcContext, OpcEvent)	(Inherited from OpcNode)
UpdateChanges(OpcContext, OpcNodeChanges)	Notifies about the `changes` on behalf of the node and removes pending changes which intersect with the `changes` specified. (Inherited from OpcNode)

Name	Description
UpdateChanges(OpcContext, OpcNodeChanges, Boolean)	Notifies about the `changes` on behalf of the node (and optionally on its children) and removes pending changes which intersect with the `changes` specified. (Inherited from OpcNode)
WriteAttributeValueCore``1(OpcWriteAttributeValueContext, OpcAttributeValue)	(Inherited from OpcNode)

Table of Contents

Constructors 1
Events 1
Properties 2
Methods 3