

# OpcMethodContext Class

**Namespace:** Opc.UaFx

**Assemblies:** Opc.UaFx.Advanced.dll

Provides information and services about the system which belong to the current method call situation.

**C#**

```
public class OpcMethodContext : OpcNodeContext<OpcMethodNode>, IOpcNamespaceResolver
```

**Inheritance** [Object](#) > [OpcContext](#) > [OpcNodeContext<OpcMethodNode>](#) > [OpcMethodContext](#)

**Implements** [IOpcNamespaceResolver](#)

## Properties

| Name                             | Description                                                                                                                                                                                  |
|----------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <a href="#">Empty</a>            | Gets an empty <a href="#">OpcContext</a> which can be used in cases there a session nor system specific context is not necessarily required.<br>(Inherited from <a href="#">OpcContext</a> ) |
| <a href="#">Identity</a>         | Gets the <a href="#">OpcUserIdentity</a> which belongs to the situation represented.<br>(Inherited from <a href="#">OpcContext</a> )                                                         |
| <a href="#">Namespaces</a>       | Gets a read-only collection of namespaces valid in the current <a href="#">OpcContext</a> .<br>(Inherited from <a href="#">OpcContext</a> )                                                  |
| <a href="#">NodeIdFactory</a>    | Gets the <a href="#">OpcNodeIdFactory</a> used to create new node identifiers using this context.<br>(Inherited from <a href="#">OpcContext</a> )                                            |
| <a href="#">Owner</a>            | Gets the owner of the current <a href="#">OpcContext</a> .<br>(Inherited from <a href="#">OpcContext</a> )                                                                                   |
| <a href="#">PreferredLocales</a> | Gets a collection of preferred locales (see <a href="#">CultureInfo.Name</a> ) to use to localize data and information.<br>(Inherited from <a href="#">OpcContext</a> )                      |
| <a href="#">Result</a>           | Gets or sets the <a href="#">OpcResult</a> determining the outcome of the callback routine.                                                                                                  |
| <a href="#">SessionId</a>        | Gets the session identifier which identifies the session within that the context has been created and is valid.<br>(Inherited from <a href="#">OpcContext</a> )                              |
| <a href="#">Target</a>           | Gets the target <a href="#">Object</a> to that the method call does belong.                                                                                                                  |



# Table of Contents

|                         |   |
|-------------------------|---|
| <b>Properties</b> ..... | 1 |
|-------------------------|---|