

OpcNodeldPropertyNode Class

Namespace: Opc.UaFx

Assemblies: Opc.UaFx.Advanced.dll

Defines a property node for node identifiers.

C#

```
public class OpcNodeIdPropertyNode : OpcPropertyNode, IOpcNode, IOpcNodeInfo
```

Inheritance Object > OpcNode > OpcInstanceNode > OpcVariableNode > OpcPropertyNode > OpcNodeldPropertyNode

Implements IOpcNode, IOpcNodeInfo

Constructors

Name	Description
OpcNodeldPropertyNode(IOpcNode, OpcName)	Initializes a new instance of the OpcNodeldPropertyNode class accessible by the <code>name</code> specified as a child node of the <code>parent</code> node given.
OpcNodeldPropertyNode(IOpcNode, OpcName, OpcNodeld)	Initializes a new instance of the OpcNodeldPropertyNode class accessible by the <code>name</code> and <code>id</code> specified as a child node of the <code>parent</code> node given.
OpcNodeldPropertyNode(IOpcNode, OpcName, OpcNodeld, OpcNodeld)	Initializes a new instance of the OpcNodeldPropertyNode class accessible by the <code>name</code> and <code>id</code> specified with the initial value defined by <code>value</code> as a child node of the <code>parent</code> node given.
OpcNodeldPropertyNode(OpcName)	Initializes a new instance of the OpcNodeldPropertyNode class accessible by the <code>name</code> specified.
OpcNodeldPropertyNode(OpcName, OpcNodeld)	Initializes a new instance of the OpcNodeldPropertyNode class accessible by the <code>name</code> and <code>id</code> specified.
OpcNodeldPropertyNode(OpcName, OpcNodeld, OpcNodeld)	Initializes a new instance of the OpcNodeldPropertyNode class accessible by the <code>name</code> and <code>id</code> specified with the initial value given by <code>value</code> .

Events

Name	Description
AfterApplyChanges	Occurs after one or more changes on the node has been notified. (Inherited from OpcNode)
BeforeApplyChanges	Occurs before one or more changes on the node are notified. (Inherited from OpcNode)

Properties

Name	Description
AccessLevel	Gets or sets a value which indicates in which ways the Value attribute of the variable node can be accessed (read/write) and if it provides current and/or historic data. (Inherited from OpcVariableNode)
ArrayDimensions	Gets the number/lengths of dimensions for an array Value with one or more fixed dimensions. (Inherited from OpcVariableNode)
Category	Gets the NodeCategoryOpcAttribute which identifies the kind of node and is therefore used to classify the node regarding its use and purpose. (Inherited from OpcNode)
DataType	Gets or sets a value which defines a pre-defined used DataTypeld as one of the members defined by the OpcDataType enumeration to simplify querying standard data types. (Inherited from OpcVariableNode)
DataTypeld	Gets or stets the identifier which identifies the node that defines the type of data represented by the variable node. (Inherited from OpcVariableNode)
DefaultReferenceTypeld	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node. (Inherited from OpcInstanceNode)
DefaultReferenceTypeld	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node. (Inherited from OpcVariableNode)
DefaultReferenceTypeld	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node. (Inherited from OpcPropertyNode)
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcInstanceNode)
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcVariableNode)
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcPropertyNode)
Description	Gets or sets the value of the optional DescriptionOpcAttribute which shall explain the meaning of the node. (Inherited from OpcNode)
Descriptions	Gets the OpcNodeGlobalization instance used to control the localization and other globalization related tasks for the Description attribute of the current node. (Inherited from OpcNode)
DisplayName	Gets or sets the value of the DisplayNameOpcAttribute which defines the localizable name of the node. (Inherited from OpcNode)

Name	Description
DisplayNames	Gets the OpcNodeGlobalization instance used to control the localization and other globalization related tasks for the DisplayName attribute of the current node. (Inherited from OpcNode)
HasPendingChanges	Gets a value indicating whether there exists any pending change on the node. (Inherited from OpcNode)
HistoryConfiguration	(Inherited from OpcVariableNode)
Id	Gets the value of the NodeIdOpcAttribute which unambiguously identifies the node. (Inherited from OpcNode)
IsArray	Gets a value indicating whether the Value of the OpcVariableNode represented is an array. (Inherited from OpcVariableNode)
IsHistorizing	(Inherited from OpcVariableNode)
ModellingRuleId	Gets or sets the identifier which defines how the OpcInstanceNode is used for instantiation. (Inherited from OpcInstanceNode)
Name	Gets or sets the value of the BrowseNameOpcAttribute which defines the non-localizable human-readable name used when browsing the address space. (Inherited from OpcNode)
Namespace	(Inherited from OpcNode)
Parent	Gets the parent node of the node. (Inherited from OpcNode)
Parent	Gets the parent node of the node. (Inherited from OpcInstanceNode)
PendingChanges	Gets a value indicating the most recent changes performed on the node since their last notification. (Inherited from OpcNode)
QueryEventsCallback	Gets or sets a callback used to query any event information which belongs to the node. (Inherited from OpcNode)
ReadAccessLevelCallback	(Inherited from OpcVariableNode)
ReadArrayDimensionsCallback	(Inherited from OpcVariableNode)
ReadDataTypeCallback	(Inherited from OpcVariableNode)
ReadDescriptionCallback	(Inherited from OpcNode)
ReadDisplayNameCallback	(Inherited from OpcNode)
ReadIsHistorizingCallback	(Inherited from OpcVariableNode)
ReadNodeIdPropertyValueCallback	Gets or sets a callback used to read the node identifier property value.
ReadPropertyValueCallback	Gets or sets a callback used to read the property value. (Inherited from OpcPropertyNameode)
ReadUserAccessLevelCallback	(Inherited from OpcVariableNode)
ReadUserWriteAccessCallback	(Inherited from OpcNode)
ReadValueRankCallback	(Inherited from OpcVariableNode)
ReadVariableValueCallback	Gets or sets a callback used to read the variable value. (Inherited from OpcVariableNode)
ReadWriteAccessCallback	(Inherited from OpcNode)
ReferenceType	Gets a value which defines a pre-defined used ReferenceTypeld as one of the members defined by the OpcReferenceType enumeration to simplify querying standard reference types. (Inherited from OpcInstanceNode)

Name	Description
ReferenceTypeId	Gets or sets the identifier which identifies the node that defines the semantic of the reference between a source and a target node and generally reflects an operation between the two, such as "A contains B". (Inherited from OpcInstanceStateNode)
Status	(Inherited from OpcVariableNode)
SymbolicName	(Inherited from OpcNode)
Tag	Gets or sets the object that contains additional user data about the node. (Inherited from OpcNode)
Timestamp	(Inherited from OpcVariableNode)
TypeDefinitionId	Gets or sets the identifier which identifies the node that defines the underlying node type from that this OpcInstanceStateNode has been created. (Inherited from OpcInstanceStateNode)
UserAccessLevel	Gets or sets a value which indicates in which ways the Value attribute of the variable node can be accessed (read/write) and if it provides current and/or historic data taking user access rights into account. (Inherited from OpcVariableNode)
UserWriteAccess	Gets or sets the value of the optional UserWriteAccessOpcAttribute which exposes the possibilities of a client to write the attributes of the node taking user access rights into account. (Inherited from OpcNode)
Value	Gets or sets the value of the property node.
Value	Gets or sets the value of the variable node which may be simple or complex. (Inherited from OpcVariableNode)
ValueRank	(Inherited from OpcVariableNode)
WriteAccess	Gets or sets the value of the optional WriteAccessOpcAttribute which exposes the possibilities of a client to write the attributes of the node. (Inherited from OpcNode)
WriteAccessLevelCallback	(Inherited from OpcVariableNode)
WriteArrayDimensionsCallback	(Inherited from OpcVariableNode)
WriteDataTypeCallback	(Inherited from OpcVariableNode)
WriteDescriptionCallback	(Inherited from OpcNode)
WriteDisplayNameCallback	(Inherited from OpcNode)
WriteIsHistorizingCallback	(Inherited from OpcVariableNode)
WriteNodeIdPropertyValueCallback	Gets or sets a callback used to write the node identifier property value.
WritePropertyValueCallback	Gets or sets a callback used to write the property value. (Inherited from OpcPropertyNameode)
WriteUserAccessLevelCallback	(Inherited from OpcVariableNode)
WriteUserWriteAccessCallback	(Inherited from OpcNode)
WriteValueRankCallback	(Inherited from OpcVariableNode)
WriteVariableValueCallback	Gets or sets a callback used to write the variable value. (Inherited from OpcVariableNode)
WriteWriteAccessCallback	(Inherited from OpcNode)

Methods

Name	Description
AddChild(OpcContext, OpcInstanceNode)	(Inherited from OpcInstanceNode)
AddNotifier(OpcContext, IOpcNode)	(Inherited from OpcNode)
ApplyChanges(OpcContext)	Notifies about changes performed on the node since the last notification and resets the pending changes to None . (Inherited from OpcNode)
ApplyChanges(OpcContext, Boolean)	Notifies about changes performed on the node (and optionally on its children) since the last notification and resets the pending changes to None . (Inherited from OpcNode)
AttributeValue(OpcAttribute)	Retrieves the value of the attribute specified. (Inherited from OpcNode)
AttributeValue``1(OpcAttribute)	Retrieves the value of the attribute specified. (Inherited from OpcNode)
Child(OpcContext, OpcName)	Retrieves the child node its Name property matches exactly the name specified. (Inherited from OpcNode)
Children(OpcContext)	Retrieves a sequence of all nodes organized as children of this node. (Inherited from OpcNode)
InitializeDefaults	Initializes the default values used by the node implementation represented / required. (Inherited from OpcNode)
InitializeDefaults	Initializes the default values used by the OpcInstanceNode. (Inherited from OpcInstanceNode)
InitializeDefaults	Initializes the default values used by the OpcVariableNode. (Inherited from OpcVariableNode)
IsChangePending(OpcNodeChanges)	(Inherited from OpcNode)
OnAfterApplyChanges(OpcNodeChangesEventArgs)	Raises the AfterApplyChanges event using the event data specified. (Inherited from OpcNode)
OnBeforeApplyChanges(OpcNodeChangesEventArgs)	Raises the BeforeApplyChanges event using the event data specified. (Inherited from OpcNode)
QueryEventsCore(OpcNodeContext, OpcEventCollection)	(Inherited from OpcNode)

Name	Description
ReadAttributeValueCore` `1(OpcReadAttributeValueContext, OpcAttributeValue)	(Inherited from OpcNode)
ReadAttributeValueCore` `1(OpcReadAttributeValueContext, OpcAttributeValue)	(Inherited from OpcVariableNode)
ReadNodeIdPropertyValueCore(OpcReadPropertyValueContext, OpcPropertyValue)	Reads the node identifier value of the property node using the context and value information specified.
ReadNodeIdValue(OpcReadVariableValueContext)	Reads the node identifier value of the property node.
ReadPropertyValueCore(OpcReadPropertyValueContext, OpcPropertyValue)	Reads the value of the property node using the context and value information specified.
ReadPropertyValueCore(OpcReadPropertyValueContext, OpcPropertyValue)	Reads the value of the property node using the context and value information specified. (Inherited from OpcPropertyNameode)
ReadValue(OpcReadVariableValueContext)	Reads the variable node value using the context specified. (Inherited from OpcVariableNode)
ReadVariableValue(OpcReadVariableValueContext)	(Inherited from OpcVariableNode)
ReadVariableValueCore(OpcReadVariableValueContext, OpcVariableValue)	Reads the value of the variable node using the context and value information specified. (Inherited from OpcVariableNode)
ReadVariableValueCore(OpcReadVariableValueContext, OpcVariableValue)	Reads the value of the variable node using the context and value information specified. (Inherited from OpcPropertyNameode)
RemoveChild(OpcContext, OpcInstanceNode)	(Inherited from OpcInstanceNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcInstanceNode)
ReportEvent(OpcContext, OpcEvent)	(Inherited from OpcNode)
UpdateChanges(OpcContext, OpcNodeChanges)	Notifies about the changes on behalf of the node and removes pending changes which intersect with the changes specified. (Inherited from OpcNode)
UpdateChanges(OpcContext, OpcNodeChanges, Boolean)	Notifies about the changes on behalf of the node (and optionally on its children) and removes pending changes which intersect with the changes specified. (Inherited from OpcNode)

Name	Description
WriteAttributeValueCore``1(OpcWriteAttributeValueContext, OpcAttributeValue)	(Inherited from OpcNode)
WriteAttributeValueCore``1(OpcWriteAttributeValueContext, OpcAttributeValue)	(Inherited from OpcVariableNode)
WriteNodIdPropertyValueCore(OpcWritePropertyValueContext, OpcPropertyValue)	Writes the node identifier value of the property node using the context and value information specified.
WriteNodIdValue(OpcWriteVariableValueContext, OpcNodId)	Writes the value of the property node specified by value .
WritePropertyValueCore(OpcWritePropertyValueContext, OpcPropertyValue)	Writes the value of the property node using the context and value information specified.
WritePropertyValueCore(OpcWritePropertyValueContext, OpcPropertyValue)	Writes the value of the property node using the context and value information specified. (Inherited from OpcPropertyNameode)
WriteValue(OpcWriteVariableValueContext, Object)	Writes the value to the variable node value using the context specified. (Inherited from OpcVariableNode)
WriteVariableValue(OpcWriteVariableValueContext, OpcVariableValue)	(Inherited from OpcVariableNode)
WriteVariableValueCore(OpcWriteVariableValueContext, OpcVariableValue)	Writes the value of the variable node using the context and value information specified. (Inherited from OpcVariableNode)
WriteVariableValueCore(OpcWriteVariableValueContext, OpcVariableValue)	Writes the value of the variable node using the context and value information specified. (Inherited from OpcPropertyNameode)

Table of Contents

Constructors	1
Events	1
Properties	1
Methods	5