

OpcStatusCodeCollection Class

Namespace: Opc.UaFx

Assemblies: Opc.UaFx.Advanced.dll

Represents a collection of [OpcStatusCode](#) instances.

C#

```
public class OpcStatusCodeCollection : OpcCollection<OpcStatusCode, StatusCode,
StatusCodeCollection>, IList<OpcStatusCode>, ICollection<OpcStatusCode>, IList, ICollection,
IReadOnlyList<OpcStatusCode>, IReadOnlyCollection<OpcStatusCode>, IEnumerable<OpcStatusCode>,
IEnumerable
```

Inheritance [Object](#) > [Collection<OpcStatusCode>](#) > [OpcCollection<OpcStatusCode, StatusCode, StatusCodeCollection>](#) > [OpcStatusCodeCollection](#)

Implements [IList<OpcStatusCode>](#), [ICollection<OpcStatusCode>](#), [IList](#), [ICollection](#), [IReadOnlyList<OpcStatusCode>](#), [IReadOnlyCollection<OpcStatusCode>](#), [IEnumerable<OpcStatusCode>](#), [IEnumerable](#)

Constructors

Name	Description
OpcStatusCodeCollection	Initializes a new instance of the OpcStatusCodeCollection class.
OpcStatusCodeCollection(IEnumerable)	Initializes a new instance of the OpcStatusCodeCollection class with the items specified.
OpcStatusCodeCollection(IEnumerable)	Initializes a new instance of the OpcStatusCodeCollection class with the statusCode specified.
OpcStatusCodeCollection(IList)	Initializes a new instance of the OpcStatusCodeCollection class as a wrapper for the specified list .
OpcStatusCodeCollection(OpcStatusCode)	Initializes a new instance of the OpcStatusCodeCollection class with the items specified.
OpcStatusCodeCollection(OpcStatusCode)	Initializes a new instance of the OpcStatusCodeCollection class with the statusCode specified.

Methods

Name	Description
Add(OpcStatusCode)	Adds a new item to the end of the collection using the statusCode specified.
Create(OpcStatusCode, Int32)	Creates a new instance of the OpcStatusCodeCollection with a initial number of items defined by count , where each item represents an instance of the OpcStatusCode class initialized using the statusCode passed.

Table of Contents

Constructors	1
Methods	1