OpcTimedShelveMethodNode Class

Namespace: Opc.UaFx
Assemblies: Opc.UaFx.Advanced.dll

Defines a method node to transition a condition into the timed shelved state.

C#

```
public class OpcTimedShelveMethodNode : OpcMethodNode, IOpcNode, IOpcNodeInfo
```

Inheritance Object › OpcNode › OpcInstanceNode › OpcMethodNode › OpcTimedShelveMethodNode

Implements IOpcNode, IOpcNodeInfo

Remarks

The timed shelved method node is a specialization of the OpcMethodNode there its node category is Method.

Constructors

Name	Description
OpcTimedShelveMethodNode(IOpcNode, OpcName, OpcNodeId, TimedShelveCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` and `id` specified with the delegate to call defined by `callback` as a child node of the `parent` node given.
OpcTimedShelveMethodNode(IOpcNode, OpcName, OpcNodeId, TimedShelveExCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` and `id` specified with the delegate to call defined by `callback` as a child node of the `parent` node given.
OpcTimedShelveMethodNode(IOpcNode, OpcName, TimedShelveCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` specified with the TimedShelveCallback call given by `callback` as a child node of the `parent` node given.
OpcTimedShelveMethodNode(IOpcNode, OpcName, TimedShelveExCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` specified with the TimedShelveExCallback call given by `callback` as a child node of the `parent` node given.
OpcTimedShelveMethodNode(OpcName, OpcNodeId, TimedShelveCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` and `id` specified with the delegate to call given by `callback`.

Name	Description
OpcTimedShelveMethodNode(OpcName, OpcNodeId, TimedShelveExCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` and `id` specified with the delegate to call given by `callback`.
OpcTimedShelveMethodNode(OpcName, TimedShelveCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` specified with the TimedShelveCallback call given by `callback`.
OpcTimedShelveMethodNode(OpcName, TimedShelveExCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class accessible by the `name` specified with the TimedShelveExCallback call given by `callback`.
OpcTimedShelveMethodNode(TimedShelveCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class with the TimedShelveCallback call given by `callback`.
OpcTimedShelveMethodNode(TimedShelveExCallback)	Initializes a new instance of the OpcTimedShelveMethodNode class with the TimedShelveExCallback call given by `callback`.

Events

Name	Description
AfterApplyChanges	Occurs after one or more changes on the node has been notified. (Inherited from OpcNode)
BeforeApplyChanges	Occurs before one or more changes on the node are notified. (Inherited from OpcNode)

Properties

Name	Description
Callback	Gets the Delegate of the method to invoke in case there this method node is called. (Inherited from OpcMethodNode)
CanExecute	Gets or sets a value indicating whether the method can be called. (Inherited from OpcMethodNode)
CanUserExecute	Gets or sets a value indicating whether the method can be called by the current user. (Inherited from OpcMethodNode)
Category	Gets the NodeCategoryOpcAttribute which identifies the kind of node and is therefore used to classify the node regarding its use and purpose. (Inherited from OpcNode)
Command	Gets the IOpcMethodCommand of the method to invoke in case there this method node is called. (Inherited from OpcMethodNode)
DefaultReferenceTypeId	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node. (Inherited from OpcInstanceNode)

Name	Description
DefaultReferenceTypeId	Gets the default identifier which identifies the type that defines the underlying node reference within this OpcInstanceNode is referenced by its parent node. (Inherited from OpcMethodNode)
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created.
DefaultTypeDefinitionId	Gets the default identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcInstanceNode)
Description	Gets or sets the value of the optional DescriptionOpcAttribute which shall explain the meaning of the node. (Inherited from OpcNode)
Descriptions	Gets the OpcNodeGlobalization instance used to control the localization and other globalization related tasks for the Description attribute of the current node. (Inherited from OpcNode)
DisplayName	Gets or sets the value of the DisplayNameOpcAttribute which defines the localizable name of the node. (Inherited from OpcNode)
DisplayNames	Gets the OpcNodeGlobalization instance used to control the localization and other globalization related tasks for the DisplayName attribute of the current node. (Inherited from OpcNode)
HasPendingChanges	Gets a value indiciating whether there exists any pending change on the node. (Inherited from OpcNode)
Id	Gets the value of the NodeIdOpcAttribute which unambiguously identifies the node. (Inherited from OpcNode)
InputArguments	Gets a read-only collection of OpcArgument instances representing the arguments consumed by the method node. (Inherited from OpcMethodNode)
ModellingRuleId	Gets or sets the identifier which defines how the OpcInstanceNode is used for instantiation. (Inherited from OpcInstanceNode)
Name	Gets or sets the value of the BrowseNameOpcAttribute which defines the non-localizable human-readable name used when browsing the address space. (Inherited from OpcNode)
Namespace	(Inherited from OpcNode)
OutputArguments	Gets a read-only collection of OpcArgument instances representing the arguments produced by the method node. (Inherited from OpcMethodNode)
Parent	Gets the parent node of the node. (Inherited from OpcNode)
Parent	Gets the parent node of the node. (Inherited from OpcInstanceNode)
PendingChanges	Gets a value indicating the most recent changes performed on the node since their last notification. (Inherited from OpcNode)
QueryEventsCallback	Gets or sets a callback used to query any event information which belongs to the node. (Inherited from OpcNode)

Name	Description
ReadDescriptionCallback	(Inherited from OpcNode)
ReadDisplayNameCallback	(Inherited from OpcNode)
ReadUserWriteAccessCallback	(Inherited from OpcNode)
ReadWriteAccessCallback	(Inherited from OpcNode)
ReferenceType	Gets a value which defines a pre-defined used ReferenceTypeId as one of the members defined by the OpcReferenceType enumeration to simplify querying standard reference types. (Inherited from OpcInstanceNode)
ReferenceTypeId	Gets or sets the identifier which identifies the node that defines the semantic of the reference between a source and a target node and generally reflects an operation between the two, such as “A contains B”. (Inherited from OpcInstanceNode)
SymbolicName	(Inherited from OpcNode)
Tag	Gets or sets the object that contains additional user data about the node. (Inherited from OpcNode)
TypeDefinitionId	Gets or sets the identifier which identifies the node that defines the underlying node type from that this OpcInstanceNode has been created. (Inherited from OpcInstanceNode)
UserWriteAccess	Gets or sets the value of the optional UserWriteAccessOpcAttribute which exposes the possibilities of a client to write the attributes of the node taking user access rights into account. (Inherited from OpcNode)
WriteAccess	Gets or sets the value of the optional WriteAccessOpcAttribute which exposes the posibilities of a client to write the attributes of the node. (Inherited from OpcNode)
WriteDescriptionCallback	(Inherited from OpcNode)
WriteDisplayNameCallback	(Inherited from OpcNode)
WriteUserWriteAccessCallback	(Inherited from OpcNode)
WriteWriteAccessCallback	(Inherited from OpcNode)

Methods

Name	Description
AddChild(OpcContext, OpcInstanceNode)	(Inherited from OpcInstanceNode)
AddNotifier(OpcContext, IOpcNode)	(Inherited from OpcNode)
ApplyChanges(OpcContext)	Notifies about changes performed on the node since the last notification and resets the pending changes to None. (Inherited from OpcNode)
ApplyChanges(OpcContext, Boolean)	Notifies about changes performed on the node (and optionally on its children) since the last notification and resets the pending changes to None. (Inherited from OpcNode)
AttributeValue(OpcAttribute)	Retrieves the value of the `attribute` specified. (Inherited from OpcNode)
AttributeValue``1(OpcAttribute)	Retrieves the value of the `attribute` specified. (Inherited from OpcNode)

Name	Description
Child(OpcContext, OpcName)	Retrieves the child node its Name property matches exactly the `name` specified. (Inherited from OpcNode)
Children(OpcContext)	Retrieves a sequence of all nodes organized as children of this node. (Inherited from OpcNode)
InitializeDefaults	Initializes the default values used by the node implementation represented / required. (Inherited from OpcNode)
InitializeDefaults	Initializes the default values used by the OpcInstanceNode. (Inherited from OpcInstanceNode)
InitializeDefaults	Initializes the default values used by the OpcInstanceNode. (Inherited from OpcMethodNode)
IsChangePending(OpcNodeChanges)	(Inherited from OpcNode)
OnAfterApplyChanges(OpcNodeChangesEventArgs)	Raises the AfterApplyChanges event using the event data specified. (Inherited from OpcNode)
OnBeforeApplyChanges(OpcNodeChangesEventArgs)	Raises the BeforeApplyChanges event using the event data specified. (Inherited from OpcNode)
QueryEventsCore(OpcNodeContext, OpcEventCollection)	(Inherited from OpcNode)
ReadAttributeValueCore``1(OpcReadAttributeValueContext, OpcAttributeValue)	(Inherited from OpcNode)
ReadAttributeValueCore``1(OpcReadAttributeValueContext, OpcAttributeValue)	(Inherited from OpcMethodNode)
RemoveChild(OpcContext, OpcInstanceNode)	(Inherited from OpcInstanceNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcNode)
RemoveNotifier(OpcContext, IOpcNode)	(Inherited from OpcInstanceNode)
ReportEvent(OpcContext, OpcEvent)	(Inherited from OpcNode)
UpdateChanges(OpcContext, OpcNodeChanges)	Notifies about the `changes` on behalf of the node and removes pending changes which intersect with the `changes` specified. (Inherited from OpcNode)
UpdateChanges(OpcContext, OpcNodeChanges, Boolean)	Notifies about the `changes` on behalf of the node (and optionally on its children) and removes pending changes which intersect with the `changes` specified. (Inherited from OpcNode)
WriteAttributeValueCore``1(OpcWriteAttributeValueContext, OpcAttributeValue)	(Inherited from OpcNode)
WriteAttributeValueCore``1(OpcWriteAttributeValueContext, OpcAttributeValue)	(Inherited from OpcMethodNode)

Table of Contents

Remarks 1
Constructors 1
Events 2
Properties 2
Methods 4