

# OpcTranslatePathResult Members

**Namespace:** Opc.UaFx

**Assemblies:** Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll

The [OpcTranslatePathResult](#) type exposes the following members.

## Properties

### Command

Gets the [OpcTranslatePath](#) instance from that this [OpcTranslatePathResult](#) originates from.

**C#**

```
public OpcTranslatePath Command { get; }
```

### Property Value

[OpcTranslatePath](#)

The [OpcTranslatePath](#) instance from which the [OpcTranslatePathResult](#) originates.

### Description

Gets the localized description of the result represented.

**C#**

```
public override OpcText Description { get; }
```

### Property Value

[OpcText](#)

The localized description from that the result has been created if neither a null reference (Nothing in Visual Basic) nor empty; otherwise the description associated with the [Code](#).

### NodeId

Gets the first target identifier which matches the type definition.

**C#**

```
public OpcNodeId NodeId { get; }
```

### Property Value

[OpcNodeId](#)

An instance of the [OpcNodeId](#) class representing the first target identifier which matches the type definition or a null reference (Nothing in Visual Basic) if [NodeIds](#) does not contain any target identifier.

## NodeIds

Gets a read-only collection of target identifiers resolved.

### C#

```
public OpcReadOnlyNodeIdCollection NodeIds { get; }
```

### Property Value

[OpcReadOnlyNodeIdCollection](#)

An instance of the [OpcReadOnlyNodeIdCollection](#) class with the target identifiers resolved.

# Table of Contents

|                   |   |
|-------------------|---|
| <b>Properties</b> | 1 |
| Command           | 1 |
| Description       | 1 |
| NodeId            | 1 |
| NodeIds           | 2 |

