

OpcWriteNode Class

Namespace: Opc.UaFx

Assemblies: Opc.UaFx.Advanced.dll

Defines a single command of the [IOpcWriteNodesService](#).

C#

```
public class OpcWriteNode : OpcNodeAttributeServiceCommand
```

Inheritance [Object](#) > [OpcServiceCommand](#) > [OpcNodeServiceCommand](#) > [OpcNodeAttributeServiceCommand](#) > [OpcWriteNode](#)

Constructors

Name	Description
OpcWriteNode(Int32, Int32, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId and namespaceIndex to write the value to the Value attribute.
OpcWriteNode(Int32, Int32, OpcAttribute, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId and namespaceIndex to write the value to the attribute .
OpcWriteNode(Int32, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId to write the value to the Value attribute.
OpcWriteNode(Int32, OpcAttribute, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId to write the value to the attribute .
OpcWriteNode(OpcNodeId, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId to write the value to the Value attribute.
OpcWriteNode(OpcNodeId, OpcAttribute, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId to write the value to the attribute .
OpcWriteNode(String, Int32, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId and namespaceIndex to write the value to the Value attribute.
OpcWriteNode(String, Int32, OpcAttribute, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId and namespaceIndex to write the value to the attribute .
OpcWriteNode(String, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId to write the value to the Value attribute.
OpcWriteNode(String, OpcAttribute, Object)	Initializes a new instance of the OpcWriteNode class using the specified nodeId to write the value to the attribute .

Properties

Name	Description
Attribute	Gets the OpcAttribute used to setup this command and which is used by the node attribute orientated service to operate on the node identified by the NodeId . (Inherited from OpcNodeAttributeServiceCommand)

Name	Description
NodeId	Gets the node identifier of the node on which a node orientated service have to operate on. (Inherited from OpcNodeServiceCommand)
SupportsNullNodeId	Gets a value indicating whether the OpcNodeServiceCommand supports instances of the OpcNodeId class its IsNull provides a value equals to the value true. (Inherited from OpcNodeServiceCommand)
Value	Gets the data which is to be written by the service to a specific attribute of a specific node.

Methods

Name	Description
DenyNullIdentifier(OpcNodeId, String)	Verifies whether the value is a null identifier by checking the IsNull property. (Inherited from OpcNodeServiceCommand)

Table of Contents

Constructors	1
Properties	1
Methods	2

