OpcOperationContext Class

Namespace: Opc.UaFx.Server
Assemblies: Opc.UaFx.Advanced.dll

C#

```
public class OpcOperationContext : OpcContext, IOpcNamespaceResolver
```

Inheritance Object › OpcContext › OpcOperationContext

Implements IOpcNamespaceResolver

Properties

Name	Description
ClientID	
Empty	Gets an empty OpcContext which can be used in cases there a session nor system specific context is not necessarily required. (Inherited from OpcContext)
Endpoint	
Identity	Gets the OpcUserIdentity which belongs to the situation represented. (Inherited from OpcContext)
Namespaces	Gets a read-only collection of namespaces valid in the current OpcContext. (Inherited from OpcContext)
NodeIdFactory	Gets the OpcNodeIdFactory used to create new node identifiers using this context. (Inherited from OpcContext)
OperationDeadline	
OperationStatus	
Owner	Gets the owner of the current OpcContext. (Inherited from OpcContext)
PreferredLocales	Gets a collection of preferred locales (see CultureInfo.Name) to use to localize data and information.
PreferredLocales	Gets a collection of preferred locales (see CultureInfo.Name) to use to localize data and information. (Inherited from OpcContext)
RequestId	
RequestType	
Session	
SessionId	
SessionId	Gets the session identifier which identifies the session within that the context has been created and is valid. (Inherited from OpcContext)
Socket	

Table of Contents

Properties 1