

OpcOperationContext Members

Namespace: Opc.UaFx.Server

Assemblies: Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll

The [OpcOperationContext](#) type exposes the following members.

Properties

ClientID

C#

```
public long ClientID { get; }
```

Property Value

Int64

Endpoint

C#

```
public OpcEndpointIdentity Endpoint { get; }
```

Property Value

[OpcEndpointIdentity](#)

OperationDeadline

C#

```
public DateTime OperationDeadline { get; }
```

Property Value

DateTime

OperationStatus

C#

```
public OpcStatus OperationStatus { get; }
```

Property Value

OpcStatus

PreferredLocales

Gets a collection of preferred locales (see [CultureInfo.Name](#)) to use to localize data and information.

C#

```
public override OpcLocaleCollection PreferredLocales { get; }
```

Property Value

OpcLocaleCollection

An instance of the [OpcLocaleCollection](#) class with [CultureInfo.Names](#)s of the cultures to use to localize data and information in order of this [OpcOperationContext](#).

RequestId

C#

```
public long RequestId { get; }
```

Property Value

Int64

RequestType

C#

```
public OpcRequestType RequestType { get; }
```

Property Value

OpcRequestType

Session

C#

```
public OpcSession Session { get; }
```

Property Value

OpcSession

SessionId

C#

```
public override OpcNodeId SessionId { get; }
```

Property Value

OpcNodeId

Socket

C#

```
public OpcSocketIdentity Socket { get; }
```

Property Value

OpcSocketIdentity

Table of Contents

Properties	1
ClientID	1
Endpoint	1
OperationDeadline	1
OperationStatus	1
PreferredLocales	2
RequestId	2
RequestType	2
Session	2
SessionId	3
Socket	3