OpcReadNodesHistoryRequest Members

Namespace: Opc.UaFx.Services
Assemblies: Opc.UaFx.Advanced.dll, Opc.UaFx.Advanced.dll
The OpcReadNodesHistoryRequest type exposes the following members.

Constructors

OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, HistoryReadValueId[])

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(IOpcServiceRequestHeader header, OpcReadHistoryDetails
details, params HistoryReadValueId[] commands)
```

Parameters

`header` IOpcServiceRequestHeader

`details` OpcReadHistoryDetails

`commands` HistoryReadValueId[]

Exceptions

ArgumentNullException

OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>)

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(IOpcServiceRequestHeader header, OpcReadHistoryDetails
details, IEnumerable<HistoryReadValueId> commands)
```

Parameters

`header` IOpcServiceRequestHeader

`details` OpcReadHistoryDetails

`commands` IEnumerable<HistoryReadValueId>

Exceptions

ArgumentNullException

OpcReadNodesHistoryRequest(OpcReadHistoryDetails, HistoryReadValueId[])

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(OpcReadHistoryDetails details, params HistoryReadValueId[]
commands)
```

Parameters

`details` OpcReadHistoryDetails

`commands` HistoryReadValueId[]

Exceptions

ArgumentNullException

OpcReadNodesHistoryRequest(OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>)

C#

```
[CLSCompliant(false)]
public OpcReadNodesHistoryRequest(OpcReadHistoryDetails details,
IEnumerable<HistoryReadValueId> commands)
```

Parameters

`details` OpcReadHistoryDetails

`commands` IEnumerable<HistoryReadValueId>

Exceptions

ArgumentNullException

Properties

Details

C#

```
public OpcReadHistoryDetails Details { get; }
```

Property Value

OpcReadHistoryDetails

ReleaseContinuationPoints

C#

```
public bool ReleaseContinuationPoints { get; set; }
```

Property Value

Boolean

TimestampsToReturn

Gets or sets a value which specifies the timestamps to be returned for each requested Value attribute.

C#

```
public OpcTimestampsToReturn TimestampsToReturn { get; set; }
```

Property Value

OpcTimestampsToReturn

One of the members defined by the OpcTimestampsToReturn enumeration except Neither.

Remarks

Using the value Neither as the timestamps to return is not valid and results into a response with the status code BadInvalidTimestampArgument.

Table of Contents

Constructors 1
OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, HistoryReadValueId[]) 1
OpcReadNodesHistoryRequest(IOpcServiceRequestHeader, OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>) 1
OpcReadNodesHistoryRequest(OpcReadHistoryDetails, HistoryReadValueId[]) 2
OpcReadNodesHistoryRequest(OpcReadHistoryDetails, IEnumerable<HistoryReadValueId>) 2
Properties 3
Details 3
ReleaseContinuationPoints 3
TimestampsToReturn 3