

# Rfc1006Client Constructor (Rfc1006IPEndPoint, Int32)

Initializes a new instance of the [Rfc1006Client](#) class using the specified *endPoint* and *aliveTime* information.

**Namespace:** [Rfc1006LibNet.Advanced](#)

**Assembly:** Rfc1006LibNet.Advanced (in Rfc1006LibNet.Advanced.dll) Version: 1.0.2.0 (1.0.5.3)

## Syntax

**C#**

```
public Rfc1006Client(
    Rfc1006IPEndPoint endPoint,
    int aliveTime
)
```

## Parameters

*endPoint*

Type: [Rfc1006LibNet.Advanced.Rfc1006IPEndPoint](#)

The [Rfc1006IPEndPoint](#) class to use to identifier the server

*aliveTime*

Type: [System.Int32](#)

The timeout in milliseconds

## Exceptions

| Exception                                   | Condition                                                          |
|---------------------------------------------|--------------------------------------------------------------------|
| <a href="#">ArgumentNullException</a>       | The <i>endPoint</i> is a null reference (Nothing in Visual Basic). |
| <a href="#">ArgumentOutOfRangeException</a> | The <i>aliveTime</i> is lower than zero.                           |

## See Also

### Reference

[Rfc1006Client Class](#)

[Rfc1006Client Overload](#)

[Rfc1006LibNet.Advanced Namespace](#)



# Table of Contents

|                   |   |
|-------------------|---|
| <b>Syntax</b>     | 1 |
| Parameters        | 1 |
| <b>Exceptions</b> | 1 |
| <b>See Also</b>   | 1 |
| Reference         | 1 |