Rfc1006Client Constructor (Int32, IPAddress, String, String, Int32)

Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.

Namespace: Rfc1006LibNet.Advanced
Assembly: Rfc1006LibNet.Advanced (in Rfc1006LibNet.Advanced.dll) Version: 1.0.2.0 (1.0.5.3)

Syntax

C#

```
public Rfc1006Client(
    int connectionTimeout,
    IPAddress address,
    string remoteTSAP,
    string localTSAP,
    int aliveTime
)
```

Parameters

connectionTimeout
Type: System.Int32
The time in milliseconds after the connection will be closed
address
Type: System.Net.IPAddress
The IPAddress to use to identifier the server IP.
remoteTSAP
Type: System.String
To use to identifier the server TSAP.
localTSAP
Type: System.String
To use to identifier the client TSAP.
aliveTime
Type: System.Int32
The timeout in milliseconds

Exceptions

Exception	Condition
ArgumentNullException	The *address* is a null reference (Nothing in Visual Basic).
ArgumentOutOfRangeException	The *aliveTime* is lower than zero.
ArgumentOutOfRangeException	The is lower than zero.

See Also

Reference

Rfc1006Client Class
Rfc1006Client Overload
Rfc1006LibNet.Advanced Namespace

Table of Contents

Syntax 1
Parameters 1
Exceptions 1
See Also 2
Reference 2