Rfc1006Client Constructor

Overload List

—-	Name	Description
	Rfc1006Client(Rfc1006IPEndPoint)	Initializes a new instance of the Rfc1006Client class using the specified *endPoint* information.
	Rfc1006Client(Int32, Rfc1006IPEndPoint)	Initializes a new instance of the Rfc1006Client class using the specified *endPoint* and *connectionTimeout* information.
	Rfc1006Client(Rfc1006IPEndPoint, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *endPoint* and *aliveTime* information.
	Rfc1006Client(Int32, Rfc1006IPEndPoint, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *endPoint*, *connectionTimeout* and *aliveTime* information.
	Rfc1006Client(IPAddress, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP* and *localTSAP* information.
	Rfc1006Client(IPAddress, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP* and *localTSAP* information.
	Rfc1006Client(String, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP* and *localTSAP* information.
	Rfc1006Client(String, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP* and *localTSAP* information.
	Rfc1006Client(Int32, IPAddress, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information.
	Rfc1006Client(Int32, IPAddress, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information.
	Rfc1006Client(Int32, String, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information.
	Rfc1006Client(IPAddress, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(IPAddress, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP* and *localTSAP* information.
	Rfc1006Client(IPAddress, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP* and *localTSAP* information.
	Rfc1006Client(IPAddress, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(String, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *aliveTime* information.

—-	Name	Description
	Rfc1006Client(String, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified *address*, *port*, *remoteTSAP* and *localTSAP* information and DefaultConnectionTimeout.
	Rfc1006Client(String, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP* and *localTSAP* information.
	Rfc1006Client(String, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(Int32, IPAddress, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(Int32, IPAddress, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information.
	Rfc1006Client(Int32, IPAddress, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information.
	Rfc1006Client(Int32, IPAddress, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(Int32, String, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(Int32, String, Int32, Byte[], Byte[])	Initializes a new instance of the Rfc1006Client class using the specified *address*, *port*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information and DefaultAliveTime.
	Rfc1006Client(Int32, String, Int32, String, String)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *connectionTimeout* information.
	Rfc1006Client(Int32, String, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(IPAddress, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(IPAddress, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(String, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *port*, *remoteTSAP*, *localTSAP* and *aliveTime* information and DefaultAliveTime.
	Rfc1006Client(String, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(Int32, IPAddress, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.
	Rfc1006Client(Int32, IPAddress, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.

—-	Name	Description
	Rfc1006Client(Int32, String, Int32, Byte[], Byte[], Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *port*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information and DefaultAliveTime.
	Rfc1006Client(Int32, String, Int32, String, String, Int32)	Initializes a new instance of the Rfc1006Client class using the specified *address*, *remoteTSAP*, *connectionTimeout*, *localTSAP* and *aliveTime* information.

Top

See Also

Reference

Rfc1006Client Class
Rfc1006LibNet.Advanced Namespace

Table of Contents

Overload List 1
See Also 3
Reference 3