# Rfc1006IPEndPoint Constructor

## Overload List

| —- | Name | Description |
|---|---|---|
| | Rfc1006IPEndPoint(Byte[], Byte[]) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *remoteTSAP* and *localTSAP* information and the DefaultPort. |
| | Rfc1006IPEndPoint(String, String) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *remoteTSAP* and *localTSAP* information and the DefaultPort. |
| | Rfc1006IPEndPoint(Int32, Byte[], Byte[]) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *port*, *localTSAP* and *remoteTSAP* information. |
| | Rfc1006IPEndPoint(Int32, String, String) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *port*, *localTSAP* and *remoteTSAP* information. |
| | Rfc1006IPEndPoint(IPAddress, Byte[], Byte[]) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *remoteTSAP* and *localTSAP* information and the DefaultPort. |
| | Rfc1006IPEndPoint(IPAddress, String, String) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *remoteTSAP* and *localTSAP* information and the DefaultPort. |
| | Rfc1006IPEndPoint(String, Byte[], Byte[]) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *remoteTSAP* and *localTSAP* information and the DefaultPort. |
| | Rfc1006IPEndPoint(String, String, String) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *remoteTSAP* and *localTSAP* information and the DefaultPort. |
| | Rfc1006IPEndPoint(IPAddress, Int32, Byte[], Byte[]) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *port*, *localTSAP* and *remoteTSAP* information. |
| | Rfc1006IPEndPoint(IPAddress, Int32, String, String) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *port*, *localTSAP* and *remoteTSAP* information. |
| | Rfc1006IPEndPoint(String, Int32, Byte[], Byte[]) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *port*, *localTSAP* and *remoteTSAP* information. |
| | Rfc1006IPEndPoint(String, Int32, String, String) | Initializes a new instance of the Rfc1006IPEndPoint class using the specified *address*, *port*, *localTSAP* and *remoteTSAP* information. |

Top

# See Also

## Reference

Rfc1006IPEndPoint Class

# Rfc1006LibNet.Advanced Namespace

# Table of Contents

***Overload List*** ..... 1
***See Also*** ..... 1
Reference ..... 1