

PlcOutputOperand Class

Namespace: IPS7Lnk.Advanced

Assemblies: IPS7LnkNet.Advanced.dll

Represents an operand which addresses a output memory blocks within a programmable logic controller (PLC).

C#

```
[Serializable]
public class PlcOutputOperand : PlcOperand, IComparable, ISerializable,
IEquatable<PlcOperand>, IComparable<PlcOperand>, IEquatable<PlcOutputOperand>,
IComparable<PlcOutputOperand>
```

Inheritance Object > PlcIdentity > PlcOperand > PlcOutputOperand

Attributes SerializableAttribute

Implements IComparable, Serialization.ISerializable, IEquatable<PlcOperand>,
IComparable<PlcOperand>, IEquatable<PlcOutputOperand>, IComparable<PlcOutputOperand>

Constructors

Name	Description
PlcOutputOperand(Serialization.SerializationInfo, Serialization.StreamingContext)	Initializes a new instance of the PlcOutputOperand class with serialized data.

Fields

Name	Description
MaxNumber	Specifies the maximum value that can be assigned to the Number property. (Inherited from PlcOperand)
MinNumber	Specifies the minimum value that can be assigned to the Number property. (Inherited from PlcOperand)

Properties

Name	Description
Counter	Gets the operand used to access the counter memory block of the controller. (Inherited from PlcOperand)
Flag	Gets the operand used to access the flag memory block of the controller. (Inherited from PlcOperand)
Input	Gets the operand used to access the input memory block of the controller. (Inherited from PlcOperand)
Number	Gets the number associated with the operand. (Inherited from PlcOperand)

Name	Description
OriginalString	Gets the original string from that the operand was created. (Inherited from PlcOperand)
Output	Gets the operand used to access the output memory block of the controller. (Inherited from PlcOperand)
PeripheryInput	Gets the operand used to access the peripheryInput memory block of the controller. (Inherited from PlcOperand)
PeripheryOutput	Gets the operand used to access the peripheryOutput memory block of the controller. (Inherited from PlcOperand)
Standard	Gets a value indicating which PlcOperandStandard was used to create the operand. (Inherited from PlcOperand)
Timer	Gets the operand used to access the timer memory block of the controller. (Inherited from PlcOperand)
Type	Gets the type of operand represented. (Inherited from PlcOperand)

Methods

Name	Description
All	Retrieves all PlcOperand instances which can be typically addressed within a PLC including the custom data block operands used so far. (Inherited from PlcOperand)
Byte(Int32)	Creates a new PlcByteAddress from this PlcOutputOperand using the byteNumber specified.
CompareTo(Object)	Compares the current PlcOutputOperand with the other .
CompareTo(Object)	Compares the current PlcIdentity with the other . (Inherited from PlcIdentity)
CompareTo(Object)	Compares the current PlcOperand with the other . (Inherited from PlcOperand)
CompareTo(PlcOperand)	Compares the current PlcOperand with another PlcOperand . (Inherited from PlcOperand)
CompareTo(PlcOutputOperand)	Compares the current PlcOutputOperand with another PlcOutputOperand .
DataBlock(Int32)	Retrieves the according PlcDataBlockOperand using the specified number of the data block operand. (Inherited from PlcOperand)
DWord(Int32)	Creates a new PlcDWordAddress from this PlcOutputOperand using the byteNumber specified.
Equals(Object)	Determines whether the specified other is equal to this PlcOutputOperand .
Equals(Object)	Determines whether the specified other is equal to this PlcIdentity . (Inherited from PlcIdentity)
Equals(Object)	Determines whether the specified other is equal to this PlcOperand . (Inherited from PlcOperand)
Equals(PlcOperand)	Determines whether the specified other is equal to this PlcOperand . (Inherited from PlcOperand)

Name	Description
Equals(PlcOutputOperand)	Determines whether the specified other is equal to this PlcOutputOperand .
GetHashCode	Retrieves a hash code for this PlcOutputOperand .
GetHashCode	Retrieves a hash code for this PlcIdentity . (Inherited from PlcIdentity)
GetHashCode	Retrieves a hash code for this PlcOperand . (Inherited from PlcOperand)
GetObjectData(Serialization.SerializationInfo, Serialization.StreamingContext)	Sets the Serialization.SerializationInfo with information about the exception.
GetObjectData(Serialization.SerializationInfo, Serialization.StreamingContext)	Sets the Serialization.SerializationInfo with information about the exception. (Inherited from PlcIdentity)
GetObjectData(Serialization.SerializationInfo, Serialization.StreamingContext)	Sets the Serialization.SerializationInfo with information about the exception. (Inherited from PlcOperand)
GetSupportedRawTypes(PlcOperandType)	Retrieves the PlcRawType members supported by the PlcOperandType specified by type . (Inherited from PlcOperand)
IsSupported(PlcOperandType, PlcRawType)	Determines whether the specified rawType can be used to address the PLC memory identified by the PlcOperandType specified by type . (Inherited from PlcOperand)
Of(PlcOperandType)	Retrieves the according PlcOperand which matches the PlcOperandType specified. (Inherited from PlcOperand)
Parse(String)	Converts an operand string to a PlcOperand instance. (Inherited from PlcOperand)
ToString	Converts the name to its string representation. (Inherited from PlcIdentity)
ToString	Converts the operand to its string representation. (Inherited from PlcOperand)
ToString(PlcOperandStandard)	Converts the operand to its string representation using the specified standard . (Inherited from PlcOperand)
TryParse(String, PlcOperand@)	Determines whether a string is a valid operand. (Inherited from PlcOperand)
UserDefinedType(Int32)	Retrieves the according PlcUserDefinedTypeOperand using the specified number of the user defined type operand. (Inherited from PlcOperand)
Word(Int32)	Creates a new PlcWordAddress from this PlcOutputOperand using the byteNumber specified.

Operators

Name	Description
op_Equality(PlcIdentity, PlcIdentity)	Returns a value indicating whether two instances of PlcIdentity are equal. (Inherited from PlcIdentity)

Name	Description
op_Equality(PlcOperand, PlcOperand)	Returns a value indicating whether two instances of PlcOperand are equal. (Inherited from PlcOperand)
op_Equality(PlcOutputOperand, PlcOutputOperand)	Returns a value indicating whether two instances of PlcOutputOperand are equal.
op_GreaterThan(PlcIdentity, PlcIdentity)	Determines whether the first specified PlcIdentity object is greater than the second specified PlcIdentity object. (Inherited from PlcIdentity)
op_GreaterThan(PlcOperand, PlcOperand)	Determines whether the first specified PlcOperand object is greater than the second specified PlcOperand object. (Inherited from PlcOperand)
op_GreaterThan(PlcOutputOperand, PlcOutputOperand)	Determines whether the first specified PlcOutputOperand object is greater than the second specified PlcOutputOperand object. (Inherited from PlcOutputOperand)
op_GreaterThanOrEqual(PlcIdentity, PlcIdentity)	Determines whether the first specified PlcIdentity object is greater than or equal to the second specified PlcIdentity object. (Inherited from PlcIdentity)
op_GreaterThanOrEqual(PlcOperand, PlcOperand)	Determines whether the first specified PlcOperand object is greater than or equal to the second specified PlcOperand object. (Inherited from PlcOperand)
op_GreaterThanOrEqual(PlcOutputOperand, PlcOutputOperand)	Determines whether the first specified PlcOutputOperand object is greater than or equal to the second specified PlcOutputOperand object.
op_Implicit(Advanced.PlcIdentity)	Converts a string formatted as name to an PlcIdentity object. (Inherited from PlcIdentity)
op_Implicit(Advanced.PlcOperand)	Converts a string formatted as operand to an PlcOperand object. (Inherited from PlcOperand)
op_Implicit(Advanced.PlcOutputOperand)	Converts a string formatted as operand to an PlcOutputOperand object.
op_Inequality(PlcIdentity, PlcIdentity)	Returns a value indicating whether two instances of PlcIdentity are not equal. (Inherited from PlcIdentity)
op_Inequality(PlcOperand, PlcOperand)	Returns a value indicating whether two instances of PlcOperand are not equal. (Inherited from PlcOperand)
op_Inequality(PlcOutputOperand, PlcOutputOperand)	Returns a value indicating whether two instances of PlcOutputOperand are not equal.
op_LessThan(PlcIdentity, PlcIdentity)	Determines whether the first specified PlcIdentity object is less than the second specified PlcIdentity object. (Inherited from PlcIdentity)
op_LessThan(PlcOperand, PlcOperand)	Determines whether the first specified PlcOperand object is less than the second specified PlcOperand object. (Inherited from PlcOperand)

Name	Description
op_LessThan(PlcOutputOperand, PlcOutputOperand)	Determines whether the first specified PlcOutputOperand object is less than the second specified PlcOutputOperand object.
op_LessThanOrEqual(PlcIdentity, PlcIdentity)	Determines whether the first specified PlcIdentity object is less than or equal to the second PlcIdentity object. (Inherited from PlcIdentity)
op_LessThanOrEqual(PlcOperand, PlcOperand)	Determines whether the first specified PlcOperand object is less than or equal to the second PlcOperand object. (Inherited from PlcOperand)
op_LessThanOrEqual(PlcOutputOperand, PlcOutputOperand)	Determines whether the first specified PlcOutputOperand object is less than or equal to the second PlcOutputOperand object.

Table of Contents

Constructors	1
Fields	1
Properties	1
Methods	2
Operators	3