

PlcTimeType Members

Namespace: IPS7Lnk.Advanced

Assemblies: IPS7LnkNet.Advanced.dll, IPS7LnkNet.Advanced.dll

The [PlcTimeType](#) type exposes the following members.

Fields

MaxValue

Represents the largest possible value of a [PlcTimeType](#).

C#

```
public static readonly TimeSpan MaxValue
```

Field Value

[TimeSpan](#)

Remarks

The according PLC value would be: T#24D_20H_31M_23S_647MS.

MinValue

Represents the smallest possible value of a [PlcTimeType](#).

C#

```
public static readonly TimeSpan MinValue
```

Field Value

[TimeSpan](#)

Remarks

The according PLC value would be: T#0D_0H_0M_0S_0MS.

Properties

DefaultValue

Gets the type dependent default value which can be assigned to an entity of the type represented.

C#

```
public override object DefaultValue { get; }
```

Property Value

Object

The type dependent default value.

Relative

Gets the relative type declaration of type.

C#

```
public static PlcTimeType Relative { get; }
```

Property Value

PlcTimeType

The relative [PlcTimeType](#).

Methods

CreateEntity()

Creates a new [IPlcEntity](#) object which represents a concrete accessible entity of this [PlcType](#).

C#

```
public override IPlcEntity CreateEntity()
```

Returns

[IPlcEntity](#)

An instance implementing the [IPlcEntity](#) interface its [Type](#) property does refer to this [PlcType](#).

Exceptions

[NotSupportedException](#)

This pure [PlcType](#) instance can't create an entity, because it is an abstract type representation.

Of(PlcIdentity)

Retrieves the according [PlcTimeType](#) which matches the supplied type metadata.

C#

```
public static PlcTimeType Of(PlcIdentity identity)
```

Parameters

identity [PlcIdentity](#)

The [PlcIdentity](#) to which the [PlcTimeType](#) does refer.

Returns

[PlcTimeType](#)

The [PlcTimeType](#) which matches with the characteristics supplied.

Exceptions

[ArgumentException](#)

The **identity** does not provide the necessary information required to address the type of data.

[ArgumentNullException](#)

The **identity** is a null reference (Nothing in Visual Basic).

Of(PlcIdentity, PlcName)

Retrieves the according [PlcTimeType](#) which matches the supplied type metadata.

C#

```
public static PlcTimeType Of(PlcIdentity identity, PlcName name)
```

Parameters

identity [PlcIdentity](#)

The [PlcIdentity](#) to which the [PlcTimeType](#) does refer.

name [PlcName](#)

The [PlcName](#) of the [PlcType](#).

Returns

[PlcTimeType](#)

The [PlcTimeType](#) which matches with the characteristics supplied.

Exceptions

ArgumentException

The **identity** does not provide the necessary information required to address the type of data.

ArgumentNullException

The **identity** or **name** is a null reference (Nothing in Visual Basic).

Table of Contents

Fields	1
MaxValue	1
MinValue	1
Properties	1
DefaultValue	1
Relative	2
Methods	2
CreateEntity()	2
Of(PlcIdentity)	2
Of(PlcIdentity, PlcName)	3

