

VirtualDeviceConnection Members

Namespace: IPS7Lnk.Advanced

Assemblies: IPS7LnkNet.Advanced.dll, IPS7LnkNet.Advanced.dll

The [VirtualDeviceConnection](#) type exposes the following members.

Constructors

VirtualDeviceConnection(VirtualDevice)

Initializes a new instance of the [VirtualDeviceConnection](#) class using the specified **device**.

C#

```
public VirtualDeviceConnection(VirtualDevice device)
```

Parameters

device [VirtualDevice](#)

The [VirtualDevice](#) associated with the new [VirtualDeviceConnection](#).

Exceptions

[ArgumentNullException](#)

The **device** is a null reference (Nothing in Visual Basic).

Properties

IsConnected

Gets a value indicating whether the connection has been completely established to the device.

C#

```
public override bool IsConnected { get; }
```

Property Value

[Boolean](#)

The value true, if the connection has been completely established; otherwise the value false.

Exceptions

ObjectDisposedException

The connection has been disposed of.

Methods

CloseCore()

Closes an established connection to a device.

C#

```
protected override void CloseCore()
```

ConnectCore()

Fully establishes a connection to a device.

C#

```
protected override void ConnectCore()
```

CreateChannel()

Creates a new immutable channel which is used as the low level access layer of the connection.

C#

```
protected override PlcDeviceConnectionChannel CreateChannel()
```

Returns

[PlcDeviceConnectionChannel](#)

A new [VirtualDeviceConnectionChannel](#) configured with the setup of this [PlcDeviceConnection](#) and its [Device](#).

OpenCore()

Establishes a connection to a device.

C#

```
protected override void OpenCore()
```

Exceptions

[ArgumentException](#)

The endpoint type of the device associated with the connection is not supported.

ArgumentNullException

The device associated with the connection does not provide endpoint information.

ReadNodesCore(IEnumerable<PlcDataNode>)

Reads the data areas described by the **nodes** specified.

C#

```
protected override IEnumerable<object> ReadNodesCore(IEnumerable<PlcDataNode> nodes)
```

Parameters

nodes IEnumerable<PlcDataNode>

The PlcDataNode's to read.

Returns

IEnumerable<Object>

The sequence of data read.

WriteNodesCore(IEnumerable<PlcDataNode>)

When implemented in a derived class, writes the data areas described by the **nodes** specified.

C#

```
protected override void WriteNodesCore(IEnumerable<PlcDataNode> nodes)
```

Parameters

nodes IEnumerable<PlcDataNode>

The PlcDataNode's to write.

Table of Contents

Constructors	1
VirtualDeviceConnection(VirtualDevice)	1
Properties	1
IsConnected	1
Methods	2
CloseCore()	2
ConnectCore()	2
CreateChannel()	2
OpenCore()	2
ReadNodesCore(IEnumerable<PlcDataNode>)	3
WriteNodesCore(IEnumerable<PlcDataNode>)	3